## SFA-360

### High Speed Overlapping Packing Machine

# SFA-7035-2 / 6040-L

SA FWU

Automatic Two-Side Sealer (Straight In-Feed)

#### **FEATURES**

- Packing Speed :
  - A / The packing style for cans, is 2x2, 2x3, 3x4; among them, 2x2, 2x3, reaching for 80 packs every minute.
- B / The packing style for500-1250 cc PET bottles (base can be five-claw) is 2x2, 2x3, reaching for 65 packs every minute. It can mate to high-speed production operation with high-speed.
- Film applied: PE material mono-roll film, split into 2 rolls: transparent film and colorful printing location plate can be used. (This machine is suitably used for PE colorful print film packing, and it lets product have additional value). A essential tool for innovation and marketing.
- Verstile packing modes to meet the requirement of fashionable shopping mall.

- Breakthrough traditional packing way with sealing, it eliminates the poor condition of easy breaking on the sealing part.
- Heat shrinkage furnace has equilibrated heat radiation, and conveyor is composed of stainless steel for transmission. It is durable for use.
- Never hurting to the quality, it saves electricity and increases the profit.
- Safety protector is shed over outside of machine. Besides, the security inspection is designed around with safety detector and alarm system for no film condition, can turnover condition, electric eye auto tracing for print surface, etc.

11

SFA-360

#### SFA-7035-2 FEATURES

- Packing materials: PE, PVE, OPP.
- Usage: Gift boxes, goods can, special products, medicines, printing articles, books, daily necessities, electric appliances, toys, metallic tools, sporting goods, wooden wares, & tiles, etc.

#### SFA-6040-L FEATURES

- To assure the quality without being damaged, save electricity and to incerase profits.
- Heat oven for contracting will send out even heat radiation. Delivery is done by roller with durability. And the speed is controlled and driven by DC motor.



#### **SPECIFICATIONS**

MODEL	PACKING MACHINE	SHRINK TUNNEL
POWER SOURCE	3PH / 220V~380V / 50 - 60 HZ	
HP	7 HP	Electric Heating 23 KW
AIR PRESSURE	5.0~6.0 kg/cm²	-
PACKING CAPACITY	Case : 2 x 3 = 480 cans/min	5~15 m/min
FILM APPLIED	PE Transparent or Colorful Printing Film	
EFFECTIVE PACKING SIZE	L : 250 x W : 200 x H : 350 mm	L : 350 x W : 270 x H : 300 mm
MACHINE DIMENSIONS	L : 3000 x W : 1200 x H : 220 mm	L : 4000 x W : 1200 x H : 2180 mm
MACHINE WEIGHT	1000 kg	

11

SFA-7035-2 6040-L MODEL **POWER SOURCE** 3PH / 220V~380V / 50~60 HZ 5~18 time/min **POWER CAPACITY** 1~15 time/min AIR PRESSURE 5.0 kg/cm<sup>2</sup> Max. L x Min. L - 500 x 200 mm PACKING SIZE Max. W x Min. W - 350 x 60 mm W: 550 x H: 280 mm Max. H x Min. H - 280 x 60 mm L: 1800 x W: 800 x H: 1470 mm MACHINE DIMENSIONS L: 1750 x W: 1140 x H: 1615 mm MACHINE WEIGHT 300 kg 12 KW MACHINE HEATING